



CERTIFICATE OF COMPLIANCE

Certificate Number: SGSNA/26/SZ/00166

Contract Number: 803987

Certificate Project Number: SZ-CERT260401144

Certified Product: Portable power station with inverter function (Product name: Portable Power Station)

Trademarks: GEYOTO

Model(s): YS1800-01-US-EC, YS1800-01-US-RS

Technical Data: See page 2

Certificate Holder: Geyoto Technology Limited
300 Delaware Avenue Suite 210-2207, Wilmington, DE19801, United States of America

This certificate supercedes previous certificates issued with the same certificate number. Certification is valid when products are indicated on the SGS directory of certified products at www.sgs.com or using the QR code below. This product has been certified in accordance with ISO/IEC 17065:2012, Conformity assessment — Requirements for bodies certifying products, processes and services and under the Type 3 guidelines provided in ISO/IEC 17067:2013, Conformity assessment — Fundamentals of product certification, and in accordance with:

ANSI/CAN/UL 2743:2023, 2nd Edition, dated July 3, 2018, revised April 14, 2023

UL 1778, Fifth Edition, revised April 28, 2023

CSA C22.2 No. 107.3-14, Third Edition

UL 2738, 2nd Edition, Dated January 12, 2018

Authorized by:

Effective date: 24 April 2026



Jason Wei
Certifier



Certification Body

Connectivity & Products, a division of SGS North America Inc.
620 Old Peachtree Road, Ste. 100, Suwanee, GA 30024, USA
t +1 770 570 1800 f +1 770 277 1240 www.sgs.com



CERTIFICATE OF COMPLIANCE

Certificate Number: SGSNA/26/SZ/00166

Contract Number: 803987

Certificate Project Number: SZ-CERT260401144

Technical Data:

AC Input: 100 – 120 V~, 50 / 60 Hz, 12A max., 1440W max.
 PV charge XT60 terminal: 11 - 60 V, 20 A max., 800 W max.
 PV charge 7909 terminal: 11 - 60 V, 10 A max., 400 W max.
 AC socket x4 (Inverter Mode): 100-120V~, 60Hz, 18A max., 1800W max.
 AC socket x4 (Bypass Mode): 100-120V~, 60Hz, 12A max., 1440W max.;
 Car charger output: 12.6V, 10A max., 126W max.
 XT60 terminal output: 12.6V, 30A max., 378W max.
 Car charger/XT60 port Total output: 378W
 USB-C1/C2 output: 5/9V, 3A, 12V, 2.5A, 15V, 2A, 20V, 1.5A, 30W max.
 USB-C3/C4 output: 5/9/12/15V, 3A, 20V, 5A, 28V, 5A, 140W max.
 USB-A1+A2 output: 5V, 2.4A, 12W max.
 Wireless charger output: 25W
 Total DC output: 500W max.
 Total output: 1800W max.
 Protection rating: IP20;
 Battery capacity: 1024Wh, 51,2 Vd.c., 20Ah;
 Discharge temperature range: -20-45 °C;
 Charge temperature range: 0-45°C

Certification Body

Connectivity & Products, a division of SGS North America Inc.
 620 Old Peachtree Road, Ste. 100, Suwanee, GA 30024, USA
 t +1 770 570 1800 f +1 770 277 1240 www.sgs.com